

WAY OILS

Compounded industrial oils specifically designed for use on heavily loaded machine tool slide-ways. Formulated with special extreme pressure and tackiness additives that allow tools to start with ease, reduce wear and corrosion, glide smoothly and help prevent stick-slip problems and oil being squeezed off the ways.

ISO GRADE	32	68	220
DENSITY @ 15.6°C	0.871	0.88	0.899
KINEMATIC VISCOSITY CST @ 40°C	32.1	68	210
KINEMATIC VISCOSITY CST @ 100°C	5.35	8.66	19.8
VISCOSITY INDEX	98	98	98
FLASH POINT, °C	205	233	247
POUR POINT, °C	-36	-30	-18
APPERANCE	TACKY	TACKY	TACKY

APPLICATIONS

RECOMMENDED FOR USE IN HORIZONTAL & VERTICAL SLIDE-WAYS SUCH AS:

- GRINDERS
- BORING MACHINES

In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of it's products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4



WAY OILS

APPLICATIONS

RECOMMENDED FOR USE IN HORIZONTAL & VERTICAL SLIDE-WAYS SUCH AS:

- LATCHES
- PLANERS
- SHAPERS
- SLOTTERS
- DRILLING MACHINES
- MILLING MACHINES
- SCREW MACHINES

*In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of it's products without notice.
For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4*

