

## **BLUE RAM DIESEL ENGINE OIL**

Engineered for heavy duty, on and off road operations. This formulation of Group II base stocks along with one of the most technically advanced additive systems provides cutting edge engine performance and protection, excellent piston cleanliness and outstanding anti-wear as well as corrosion, rust, foam and soot control. This 14 TBN engine oil ensures extra protetion for heavy duty diesel engines in long haul operations.

SAE GRADE	15W40
SPECIFIC GRAVITY @ 15.5°C, CST	0.8838
KINEMATIC VISCOSITY (D445) CST @ 40°C	118
KINEMATIC VISCOSITY (D445) CST @ 100°C	14.9
VISCOSITY INDEX (D2270)	137
FLASH POINT (D92), °C	225
POUR POINT (D97), °C	-42
VISCOSITY, CCS CP @ -20°C	6267
TBN	14
ASH SULPHATE, WT%	1.46
COLOUR	3

In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of it's products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4







## PRODUCT SPECIFICATION data sheet

## **BLUE RAM DIESEL ENGINE OIL**

SAE GRADE 15W40

\*NOTE: VALUES SHOWN ABOVE ARE REPRESENTATIVE OF CURRENT PRODUCTION AND MAY VARY WITHIN MODEST RANGES

## APPLICATIONS MEETS OR EXCEEDS THE FOLLOWING API SERVICE AND OEM SPECIFICATIONS REQUIREMENTS:

• API: CI-4, CH-4

• MACK: EO-N PP, EO-N PLUS

• CATERPILLAR: IN/IK

• VOLVO: VDS-2, VDS-3

• API: SL

• DETROIT DIESEL

ALLISON TRANSMISSION C-4

In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of it's products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4



