

SYNTHETIC GL-5 GEAR OIL

Specifically designed to meet the service requirements of API: GL-5 , Eaton and Rockwell differentials. Formulated for superior flow ability to minimize gear wear, reduce frictional drag and protect against heavy loading failures in extreme weather conditions.

SAE GRADE	75W90	75W140	80W140
DENSITY @ 15.5°C, KG/L	0.8695	0.8835	0.8835
KINEMATIC VISCOSITY (D445) CST @ 40°C	109.3	175.1	175.1
KINEMATIC VISCOSITY (D445) CST @ 100°C	16.5	24.85	24.85
VISCOSITY INDEX (D2270)	159	175	175
FLASH POINT (D92), °C	204	202	216
POUR POINT (D97), °C	-51	-51	-51
BROOKFIELD VISCOSITY @-40°C	135000	105000	105000

*NOTE: VALUES SHOWN ABOVE ARE REPRESENTATIVE OF CURRENT PRODUCTION AND MAY VARY WITHIN MODEST RANGES

APPLICATIONS

MEETS OR EXCEEDS THE FOLLOWING SERVICE REQUIREMENTS:

- API: GL-5
- MACK: GO-J, GO-H, GO-G

In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of it's products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4



SYNTHETIC GL-5 GEAR OIL

APPLICATIONS

MEETS OR EXCEEDS THE FOLLOWING SERVICE REQUIREMENTS:

- MT-1
- AIST/US STEEL 224
- SAE: J2360, MIL-2105E/F
- LIMITED SLIP
- ROCKWELL: 076-E
- AGMA 9005-E02: 250.03, 250.04, 251.02, NO. 4
- CEC: L-45-A-99

In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of it's products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4

