

SYNTHETIC INDUSTRIAL GEAR OIL

These synthetic gear oils are formulated with polyalphaolefin base oils and specifically selected additives for use in a vast range of enclosed gearing systems as well as plain and rolling element bearings. Extreme pressure additives provide maximum load carrying capacities and minimize gear wear, high temperature sludge, oxidation resistance, rust and corrosion protection.

SAE GRADE	100	150	220	320	460
API GRAVITY	34.97	33.61	32.46	31.14	30.4
KINEMATIC VISCOSITY (D445) CST @ 40°C	100	150	220	320	460
KINEMATIC VISCOSITY (D445) CST @ 100°C	14.5	19.6	26	34.2	44.3
VISCOSITY INDEX (D2270)	150	150	150	155	155
FLASH POINT (D92), °C	225	230	230	240	240
POUR POINT (D97), °C	-45	-45	-40	-30	-30

*NOTE: VALUES SHOWN ABOVE ARE REPRESENTATIVE OF CURRENT PRODUCTION AND MAY VARY WITHIN MODEST RANGES

APPLICATIONS

RECOMMENDED FOR ALL TYPES OF INDUSTRIAL EQUIPMENT REQUIRING EXTREME PRESSURE(EP) GEAR OIL

MEETS OR EXCEEDS THE FOLLOWING SERVICE REQUIREMENTS:

In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of it's products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4



SYNTHETIC INDUSTRIAL GEAR OIL

APPLICATIONS

RECOMMENDED FOR ALL TYPES OF INDUSTRIAL EQUIPMENT REQUIRING EXTREME PRESSURE(EP) GEAR OIL

- AGMA/ANSI: 9005-D94 EP, 9005-E02 EP
- ISO: 12925-1 TYPE CKD
- DAVID BROWN: S1.53.101
- CINCINNATI MILACRON
- DIN 51517 PART 2
- US STEEL: 224
- HANSEN TRANSMISSIONS
- M?LLER WEINGARTEN EQUIPMENT

In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of it's products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4

