

5TH WHEEL GREASE

This 5th Wheel Grease is formulated with corrosion, oxidation and anti-wear additives to provide superior plate protection. A tacky frictional modifier enhances this formulation to ensure exceptional adhesion

NLGI GRADE	5TH WHEEL GREASE
CONE PENETRATION @ 25°C (77°F), WORKED 60 STROKES	265 - 295
SOAP TYPE	LITHIUM 12 HYDROXY
SOAP CONTENT, %	8% - 12%
DROPPING POINT, °C (°F)	185°C (365°F)
BASE OIL VISCOSITY SUS @ 40°C	375 - 425
BASE OIL VISCOSITY SUS @ 100°C	60
VISCOSITY INDEX	95
COLOUR	DARK BROWN/BLACK
APPEARANCE	SMOOTH
TIMKEN OK LOAD, LBS	40 LBS

*NOTE: VALUES SHOWN ABOVE ARE REPRESENTATIVE OF CURRENT PRODUCTION AND MAY VARY WITHIN MODEST RANGES

APPLICATIONS

- DESIGNED FOR 5TH WHEEL APPLICATIONS ONLY

In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of it's products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4





5TH WHEEL GREASE

APPLICATIONS

*NOTE: FOR INITIAL GREASING, CLEAN 5TH WHEEL THOROUGHLY TO ENSURE GREASE ADHERES PROPERLY

In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of it's products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4

