

R&O TURBINE OILS

Formulated with selected premium base stocks and carefully refined to ensure exceptional performance and a long service life. This formulation includes a special additive package to ensure protection against rust and corrosion, as well as exceptional oxidation resulting in outstanding operational performance.

ISO GRADE	32	46	68	100	150	220
DENSITY @ 15.5°C	0.8614	0.865	0.8694	0.881	0.8891	0.899
KINEMATIC VISCOSITY CST @ 40°C	32	46	68	100	150	220
KINEMATIC VISCOSITY CST @ 100°C	5.4	6.8	8.9	11.4	11.8	18.8
VISCOSITY INDEX	100	105	102	102	102	120
FLASH POINT, °C	190	218	232	233	243	267
POUR POINT, °C	-36	-33	-30	-25	-25	-23
COLOR	PALE	PALE	PALE	PALE	PALE	PALE

APPLICATIONS MEETS AND EXCEEDS THE FOLLOWING REQUIREMENTS

- STEAM TURBINE SYSTEMS
- GAS TURBINE SYSTEMS

In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of its products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4



R&O TURBINE OILS

APPLICATIONS

MEETS AND EXCEEDS THE FOLLOWING REQUIREMENTS

- AIR & GAS COMPRESSORS
- CIRCULATING OILS SYSTEMS
- DIN 51524, PART (1)
- CININNATI MILACRON: P-38, P-45, P-54, P-55, P-57, P-62
- AFNOR E-48600HL
- HYDRAULIC OIL SYSTEMS THAT REQUIRE ZINC (ZN) FREE CHEMISTRY
- DENISON: HF-1
- MIL-L-17672C
- U.S STEEL 126

In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of it's products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4

